

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VELOSIT PR 301 (B)

UFI: P89A-GSTP-AFCK-07MR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Primer and mortar resin

Uses advised against

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name: VELOSIT GmbH & Co. KG
Street: Industriepark 5 - 7
Place: D-32805 Horn-Bad Meinberg
Telephone: +49 (0) 5233-9517-300 Telefax: +49 (0) 5233-9517-301
E-mail: info@velosit.de
Contact person: Technical Department
Internet: <http://www.velosit.de>
Responsible Department: Technical Department
info@velosit.de
GBK Gefahrgut Buero GmbH, Tel. +49 (0) 6132 - 84463

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Acute Tox. 4; H302
Skin Corr. 1B; H314
Eye Dam. 1; H318
Skin Sens. 1; H317
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

benzyl alcohol
4,4'-Methylenebis(aminocyclohexane)
3-aminomethyl-3,5,5-trimethylcyclohexylamine
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)
Formaldehyde, polymer with benzenamine, hydrogenated
N,N'-bis(3-aminopropyl)ethylenediamine
Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols
N-(2-aminoethyl)-1,3-propanediamine

Signal word: Danger

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 2 of 15

Pictograms:



Hazard statements

| | |
|------|--|
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary statements

| | |
|----------------|--|
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor. |

Special labelling of certain mixtures

| | |
|--------|--|
| EUH071 | Corrosive to the respiratory tract. Restricted to professional users. |
|--------|--|

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

formulated polyamine hardener

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 3 of 15

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|-------------|--|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No. 1272/2008) | | | |
| 100-51-6 | benzyl alcohol | | | 45 - < 50 % |
| | 202-859-9 | 603-057-00-5 | 01-2119492630-38 | |
| | Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B; H302 H319 H317 | | | |
| 1761-71-3 | 4,4'-Methylenebis(aminocyclohexane) | | | 10 - < 15 % |
| | 217-168-8 | | 01-2119541673-38 | |
| | Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1B, STOT RE 2; H302 H314 H318 H317 H373 | | | |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | | | 10 - < 15 % |
| | 220-666-8 | 612-067-00-9 | 01-2119514687-32 | |
| | Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317 | | | |
| 113930-69-1 | 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) | | | 10 - < 15 % |
| | 500-302-7 | | 01-2119965162-39 | |
| | Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H314 H318 H317 H411 | | | |
| 135108-88-2 | Formaldehyde, polymer with benzenamine, hydrogenated | | | 5 - < 10 % |
| | | | 01-2119983522-33 | |
| | Acute Tox. 3, Skin Corr. 1C, Skin Sens. 1, STOT RE 2, Aquatic Chronic 3; H301 H314 H317 H373 H412 | | | |
| 90-72-2 | 2,4,6-tris(dimethylaminomethyl)phenol | | | 1 - < 5 % |
| | 202-013-9 | 603-069-00-0 | 01-2119560597-27 | |
| | Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H315 H319 | | | |
| 10563-26-5 | N,N'-bis(3-aminopropyl)ethylenediamine | | | 1 - < 5 % |
| | 234-147-9 | | 01-2119976331-37 | |
| | Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1A; H311 H302 H314 H317 | | | |
| | Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols | | | 1 - < 5 % |
| | 701-443-9 | | 01-2119980970-27 | |
| | Skin Irrit. 2, Skin Sens. 1A, Aquatic Chronic 2; H315 H317 H411 | | | |
| 13531-52-7 | N-(2-aminoethyl)-1,3-propanediamine | | | < 1 % |
| | 236-882-0 | | 01-2120097861-45 | |
| | Acute Tox. 2, Acute Tox. 4, Skin Corr. 1A, Skin Sens. 1A; H310 H302 H314 H317 | | | |

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 4 of 15

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|-------------|-----------|--|-------------|
| | | Specific Conc. Limits, M-factors and ATE | |
| 100-51-6 | 202-859-9 | benzyl alcohol | 45 - < 50 % |
| | | oral: ATE 1200 mg/kg | |
| 1761-71-3 | 217-168-8 | 4,4'-Methylenebis(aminocyclohexane) | 10 - < 15 % |
| | | dermal: LD50 = 2110 mg/kg; oral: LD50 = 380 mg/kg | |
| 2855-13-2 | 220-666-8 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | 10 - < 15 % |
| | | inhalation: LC50 = >5,01 mg/l (dusts or mists); oral: ATE 1030 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100 | |
| 135108-88-2 | | Formaldehyde, polymer with benzenamine, hydrogenated | 5 - < 10 % |
| | | oral: LD50 = 300 mg/kg | |
| 90-72-2 | 202-013-9 | 2,4,6-tris(dimethylaminomethyl)phenol | 1 - < 5 % |
| | | oral: ATE = 500 mg/kg | |
| 10563-26-5 | 234-147-9 | N,N'-bis(3-aminopropyl)ethylenediamine | 1 - < 5 % |
| | | dermal: ATE = 300 mg/kg; oral: LD50 = 1140 mg/kg | |
| | 701-443-9 | Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols | 1 - < 5 % |
| | | dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg | |
| 13531-52-7 | 236-882-0 | N-(2-aminoethyl)-1,3-propanediamine | < 1 % |
| | | dermal: LD50 = 184 mg/kg; oral: LD50 = 654 mg/kg | |

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 5 of 15

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Carbon dioxide (CO₂). Foam. Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear personal protection equipment (refer to section 8). Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

Hints on joint storage

For more information about together and separate storage: refer to TRGS 510

Further information on storage conditions

Recommended storage temperature: 10 - 30 °C

Keep/Store only in original container.

Store in a dry place.

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 6 of 15

7.3. Specific end use(s)

Further remarks:

Information System of the Professional Association of construction industry see on www.gjsbau.de

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|-------------|--|----------------|----------|-------------------------|
| 100-51-6 | benzyl alcohol | | | |
| | Worker DNEL, long-term | inhalation | systemic | 22 mg/m ³ |
| | Worker DNEL, acute | inhalation | systemic | 110 mg/m ³ |
| | Worker DNEL, long-term | dermal | systemic | 8 mg/kg bw/day |
| | Worker DNEL, acute | dermal | systemic | 40 mg/kg bw/day |
| 1761-71-3 | 4,4'-Methylenebis(aminocyclohexane) | | | |
| | Worker DNEL, long-term | inhalation | systemic | 0,13 mg/m ³ |
| | Worker DNEL, long-term | dermal | systemic | 0,053 mg/kg bw/day |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | | | |
| | Worker DNEL, long-term | inhalation | local | 0,073 mg/m ³ |
| | Worker DNEL, acute | inhalation | local | 0,073 mg/m ³ |
| 113930-69-1 | 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) | | | |
| | Worker DNEL, long-term | inhalation | systemic | 0,493 mg/m ³ |
| | Worker DNEL, long-term | dermal | systemic | 0,14 mg/kg bw/day |
| 135108-88-2 | Formaldehyde, polymer with benzenamine, hydrogenated | | | |
| | Worker DNEL, long-term | inhalation | systemic | 0,2 mg/m ³ |
| | Worker DNEL, acute | inhalation | systemic | 2 mg/m ³ |
| | Worker DNEL, long-term | dermal | systemic | 2 mg/kg bw/day |
| | Worker DNEL, acute | dermal | systemic | 6 mg/kg bw/day |
| | Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols | | | |
| | Worker DNEL, long-term | inhalation | systemic | 1,21 mg/m ³ |
| | Worker DNEL, long-term | dermal | systemic | 2,87 mg/kg bw/day |
| 13531-52-7 | N-(2-aminoethyl)-1,3-propanediamine | | | |
| | Worker DNEL, long-term | inhalation | systemic | 0,62 mg/m ³ |
| | Worker DNEL, long-term | dermal | systemic | 0,18 mg/kg bw/day |

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 7 of 15

PNEC values

| CAS No | Substance | Value |
|---------------------------|--|-------------|
| Environmental compartment | | |
| 100-51-6 | benzyl alcohol | |
| | Freshwater | 1 mg/l |
| | Marine water | 0,1 mg/l |
| | Freshwater sediment | 5,27 mg/kg |
| | Marine sediment | 0,527 mg/kg |
| | Soil | 0,456 mg/kg |
| 1761-71-3 | 4,4'-Methylenebis(aminocyclohexane) | |
| | Freshwater | 0,08 mg/l |
| | Marine water | 0,008 mg/l |
| | Freshwater sediment | 137 mg/kg |
| | Marine sediment | 13,7 mg/kg |
| | Soil | 27,2 mg/kg |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | |
| | Freshwater | 0,06 mg/l |
| | Marine water | 0,006 mg/l |
| | Freshwater sediment | 5,784 mg/l |
| | Marine sediment | 0,578 mg/l |
| | Soil | 1,121 mg/l |
| 113930-69-1 | 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) | |
| | Freshwater | 0,001 mg/l |
| | Marine water | 0 mg/l |
| 135108-88-2 | Formaldehyde, polymer with benzenamine, hydrogenated | |
| | Freshwater | 0,015 mg/l |
| | Marine water | 0,002 mg/l |
| | Freshwater sediment | 15 mg/kg |
| | Marine sediment | 1,5 mg/kg |
| | Soil | 1,8 mg/kg |
| 90-72-2 | 2,4,6-tris(dimethylaminomethyl)phenol | |
| | Freshwater | 0,046 mg/l |
| | Marine water | 0,005 mg/l |
| | Freshwater sediment | 0,262 mg/kg |
| | Marine sediment | 0,026 mg/kg |
| | Soil | 0,025 mg/kg |
| | Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols | |
| | Freshwater | 0,015 mg/l |
| | Marine water | 0,014 mg/l |
| | Freshwater sediment | 1,564 mg/kg |
| | Marine sediment | 0,156 mg/kg |
| | Soil | 0,305 mg/kg |

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 8 of 15

| | | |
|---------------------|-------------------------------------|-------------|
| 13531-52-7 | N-(2-aminoethyl)-1,3-propanediamine | |
| Freshwater | | 0,144 mg/l |
| Marine water | | 0,014 mg/l |
| Freshwater sediment | | 0,648 mg/kg |
| Marine sediment | | 0,065 mg/kg |
| Soil | | 0,045 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. (EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommendation to EN 374: For short time use or protection against splashes: Butyl rubber / nitrile rubber (0.4 mm), contaminated gloves should be changed and disposed. Suitable for permanent exposure: Viton gloves (0.4 mm) Break through time > 30 min.

Skin protection

Wear suitable protective clothing. Recommendation: Safety shoes according to EN ISO 20345, long pants and long-sleeved work shirt; with mixing and stirring work additional rubber apron and protective boots according to EN 14605

Respiratory protection

To follow: EN 689 - Methods for determining inhalation exposure In case of inadequate ventilation wear respiratory protection. Organic vapor filter (Type A) The selection of respirators (EN 14387) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits (sections 8.1) of the selected respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|--------------|
| Physical state: | Liquid |
| Colour: | light yellow |
| Odour: | slightly. |

| | Test method |
|---|---------------------------|
| Melting point/freezing point: | not determined |
| Boiling point or initial boiling point and boiling range: | not determined |
| Flammability: | not determined |
| Lower explosion limits: | not determined |
| Upper explosion limits: | not determined |
| Flash point: | 94 °C calculated. |
| Auto-ignition temperature: | No information available. |
| Decomposition temperature: | No information available. |
| pH-Value: | No information available. |
| Viscosity / kinematic: | not determined |
| Water solubility: | No information available. |

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 9 of 15

Solubility in other solvents

No information available.

Dissolution rate:

not determined

Partition coefficient n-octanol/water:

No information available.

Vapour pressure:

No information available.

Density (at 23 °C):

ca. 1,02 g/cm³ ISO 2811-2

Relative vapour density:

No information available.

Particle characteristics:

not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No information available.

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate:

No information available.

Sublimation point:

not determined

Softening point:

not determined

Pour point:

not determined

Viscosity / dynamic:

< 100 mPa·s ISO 2884-1

(at 25 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Acid, Oxidising agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 849,8 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 10 of 15

| CAS No | Chemical name | | | | |
|-------------|--|------------------|----------------|--------------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 100-51-6 | benzyl alcohol | | | | |
| | oral | ATE 1200 mg/kg | | | |
| 1761-71-3 | 4,4'-Methylenebis(aminocyclohexane) | | | | |
| | oral | LD50 380 mg/kg | Rat | ECHA Dossier | |
| | dermal | LD50 2110 mg/kg | Rabbit | ECHA Dossier | |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | | | | |
| | oral | ATE 1030 mg/kg | | | |
| | inhalation (4 h) dust/mist | LC50 >5,01 mg/l | Rat (OECD 403) | ECHA Dossier | |
| 135108-88-2 | Formaldehyde, polymer with benzenamine, hydrogenated | | | | |
| | oral | LD50 300 mg/kg | Rat | ECHA Dossier | |
| 90-72-2 | 2,4,6-tris(dimethylaminomethyl)phenol | | | | |
| | oral | ATE 500 mg/kg | | | |
| 10563-26-5 | N,N'-bis(3-aminopropyl)ethylenediamine | | | | |
| | oral | LD50 1140 mg/kg | Rat | ECHA Dossier | |
| | dermal | ATE 300 mg/kg | | | |
| | Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols | | | | |
| | oral | LD50 >2000 mg/kg | Rat | ECHA Dossier | |
| | dermal | LD50 >2000 mg/kg | Rat | ECHA Dossier | |
| 13531-52-7 | N-(2-aminoethyl)-1,3-propanediamine | | | | |
| | oral | LD50 654 mg/kg | Rat | ECHA Dossier | |
| | dermal | LD50 184 mg/kg | Rabbit | | |

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Sensitising effects

May cause an allergic skin reaction. (benzyl alcohol; 4,4'-Methylenebis(aminocyclohexane); 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine); Formaldehyde, polymer with benzenamine, hydrogenated; N,N'-bis(3-aminopropyl)ethylenediamine; Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols; N-(2-aminoethyl)-1,3-propanediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 11 of 15

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.
(4,4'-Methylenebis(aminocyclohexane))

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

| CAS No | Chemical name | | | | | |
|-------------|--|------------------|-----------|--------------------------------|--------------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 1761-71-3 | 4,4'-Methylenebis(aminocyclohexane) | | | | | |
| | Acute fish toxicity | LC50 >100 mg/l | 96 h | Leuciscus idus | ECHA Dossier | |
| 135108-88-2 | Formaldehyde, polymer with benzenamine, hydrogenated | | | | | |
| | Acute fish toxicity | LC50 63 mg/l | 96 h | Poecilia reticulata (OECD 203) | ECHA Dossier | |
| | Acute algae toxicity | ErC50 43,94 mg/l | 72 h | Desmodesmus subspicatus | ECHA Dossier | |
| | Acute crustacea toxicity | EC50 18,6 mg/l | 48 h | Daphnia magna (OECD 202) | ECHA Dossier | |
| | Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols | | | | | |
| | Acute fish toxicity | LC50 5,6 mg/l | 96 h | Oryzias latipes (OECD 203) | ECHA Dossier | |
| | Acute crustacea toxicity | EC50 4,6 mg/l | 48 h | Daphnia magna (OECD 202) | ECHA Dossier | |

12.2. Persistence and degradability

The product has not been tested.

| CAS No | Chemical name | | | |
|-------------|--|-------|----|--------------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| 100-51-6 | benzyl alcohol | | | |
| | OECD 301D/ EEC 92/69/V, C.4-E | 95% | 28 | ECHA Dossier |
| | Readily biodegradable (according to OECD criteria). | | | |
| 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | | | |
| | Biodegradation | 8% | 28 | ECHA Dossier |
| | Not readily biodegradable (according to OECD criteria) | | | |
| 113930-69-1 | 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) | | | |
| | OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D | 0% | 28 | ECHA Dossier |
| | Not readily biodegradable (according to OECD criteria) | | | |

12.3. Bioaccumulative potential

The product has not been tested.

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 12 of 15

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|-------------|--|---------|
| 100-51-6 | benzyl alcohol | 1,1 |
| 1761-71-3 | 4,4'-Methylenebis(aminocyclohexane) | 2,03 |
| 113930-69-1 | 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) | 3,6 |
| 135108-88-2 | Formaldehyde, polymer with benzenamine, hydrogenated | 2,68 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|--------|--|--------|---------|--------|
| | Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols | 69-190 | | |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 13 of 15

| | |
|---|--|
| <u>14.1. UN number or ID number:</u> | UN 2735 |
| <u>14.2. UN proper shipping name:</u> | POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Methylenebis(aminocyclohexane); Isophorone diamine) |
| <u>14.3. Transport hazard class(es):</u> | 8 |
| <u>14.4. Packing group:</u> | II |
| Hazard label: | 8 |
| Classification code: | C7 |
| Special Provisions: | 274 |
| Limited quantity: | 1 L |
| Excepted quantity: | E2 |
| Transport category: | 2 |
| Hazard No: | 80 |
| Tunnel restriction code: | E |

Marine transport (IMDG)

| | |
|---|--|
| <u>14.1. UN number or ID number:</u> | UN 2735 |
| <u>14.2. UN proper shipping name:</u> | POLYAMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Methylenbis(cyclohexylamine); Isophorone diamine) |
| <u>14.3. Transport hazard class(es):</u> | 8 |
| <u>14.4. Packing group:</u> | II |
| Hazard label: | 8 |
| Marine pollutant: | No |
| Special Provisions: | 274 |
| Limited quantity: | 1 L |
| Excepted quantity: | E2 |
| EmS: | F-A, S-B |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: VOC content (g/L), delivery state: < 500

Subcategory according to Directive 2004/42/EC: Two-pack reactive performance coatings for specific end use such as floors - Solvent-borne coatings, VOC limit value: 500 g/l

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

Prohibition/Restriction:

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV): not applicable

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 14 of 15

REACH Information: All substances contained in our Products are preregistered or registered by our upstream suppliers, and/or preregistered or registered by us, and/or excluded from the regulation, and/or exempted from the registration.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

benzyl alcohol
 4,4'-Methylenebis(aminocyclohexane)
 3-aminomethyl-3,5,5-trimethylcyclohexylamine
 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)
 Reaction mass of (1-phenylethyl)phenols and bis-(1-phenylethyl)phenols

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,3.

Abbreviations and acronyms

Acute Tox. 2: Acute toxicity, hazard category 2
 Skin Corr. 1A: Skin corrosion, sub-category 1A
 Skin Irrit. 2: Skin irritation, hazard category 2
 Eye Dam. 1: Serious eye damage, hazard category 1
 Eye Irrit. 2: Eye irritation, hazard category 2
 Skin Sens. 1: Skin sensitisation, hazard category 1
 STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008

| Classification | Classification procedure |
|-------------------------|--------------------------|
| Acute Tox. 4; H302 | Calculation method |
| Skin Corr. 1B; H314 | Calculation method |
| Eye Dam. 1; H318 | Calculation method |
| Skin Sens. 1; H317 | Calculation method |
| STOT RE 2; H373 | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

Relevant H and EUH statements (number and full text)

H301 Toxic if swallowed.
 H302 Harmful if swallowed.

Safety Data Sheet

according to (EC) No 1907/2006

VELOSIT PR 301 (B)

Revision: 18.12.2025

Page 15 of 15

| | |
|--------|--|
| H310 | Fatal in contact with skin. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H373 | May cause damage to kidneys through prolonged or repeated exposure if swallowed. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)